C O N V A I R A Division of General Dynamics Corporation (San Diego)

DESIGN INFORMATION BULLETIN

NO:

19,007

CONVAIR REPORT NO. ZM-22-005

PAGE:

1 of 1

MODEL 22 AIRPLANE

DATE:

15 May 1957

LANDING GEAR RETRACTION DESIGN CONDITIONS

The following summary lists the conditions which establish the requirements for landing gear retraction:

1. Detail Model Specification (ZD-22-002):

Guaranteed maximum retraction time: 6 sec. to retract gear, an additional 4 sec. for closing landing gear door.

Total Time: 10 seconds.

- 2. (A) The hydraulic system components are calculated to meet a <u>design objective</u> of a 6 sec. gear retraction cycle, including closing doors.
 - (B) Dad conditions which are part of the above consideration are:
 - (a) Standard day, sea level, 178,500 lbs. T.O. gross wt., air speed 225 knots (max.) at completion of gear retraction cycle.
 - (b) 1.0g vertical load factor.
- 3. Structural requirements will be met and adequate hydraulic pressure will be available to provide complete gear retraction, including door closure in 10 seconds for the following conditions:
 - (a) 270 knot max. airspeed, 1.0g vert. load factor.
 - (b) 225 knot max. airspeed, 1.5g vert. load factor.

Prepared by:

E.A. Gaut, Design Engineer

Approved by:

W. Nugent, Design Grp. Engr.

A.J. Savard, Project Engr.

R.L. Benson, Weights

T. Heid, Structures

Gleanly Moore

L. Garday, Hydraulies

M Dublin, Dynamics

/.D.M. Bennett, Aerodynamics